


BOILER CONNECTIONS	
A.(1) STEAM OUTLET	6" 300# FLANGE
B.(4) LWCO	1" NPT
C.(2) BOILER BLOWDOWN	1 1/2" NPT
D.(2) SURFACE BLOWDOWN	1" NPT
G.(1) MANWAY	12" x 16"
H.(5) HANDHOLE	3" x 4"
J.(1) CLEANOUT	17" ID
K.(2) FEEDWATER	2" NPT
L.(1) AUXILIARY/VENT	2" NPT
M.(2) LOW FIRE HOLD	1/2" NPT
N.(1) STACK TEMP	1/2" NPT
P.(1) SIGHT PORT	1" PIPE

RATINGS	
NOMINAL BOILER HORSEPOWER	300
DESIGN PRESSURE	150 PSIG STEAM
GROSS OUTPUT	10043 MBH
STEAM OUTPUT (FROM & AT 212°F)	10350 LBS/HR
INPUT GAS (1,000 BTU)	12553 MBH
INPUT OIL (140,000 BTU)	89.66 GAL
INPUT OIL (150,000 BTU)	83.68 GAL

DATA	
HEATING SURFACE (ASME)	1520 SqFt
CORRUGATED FURNACE VOLUME	81.13 CuFt
STEAM STORAGE VOLUME	42.99 CuFt
STEAM RELEASE AREA	67.12 SqFt
WATER CAPACITY:	
(NWL)	2150 Gal @ 17879 Lbs
(FULL)	2471 Gal @ 20554 Lbs
SHIPPING WEIGHT:	26,700 Lbs

BOILER MODEL
MOHICAN
7-5-1500-S150



NOTES
1. SUPERIOR BOILER WORKS, INC RESERVES THE RIGHT TO CHANGE DIMENSION DUE TO PRODUCT REVISIONS OR JOB REQUIREMENTS.
2. ALL DIMENSIONS ARE APPROXIMATE AND MAY BE USED FOR LAYOUT ONLY.
3. BOILER DESIGN CODE ASME SECTION 1.
4. BOILER INSULATED WITH 2" - 8# DENSITY MINERAL FIBER INSULATION WITH 22 GAUGE STEEL JACKET.
5. ALL UNITS MANUFACTURED TO UL LISTING PROCEDURES.
7. FURNACE VOLUME IS FURNACE ONLY (WET BACKED TURNAROUND NOT INCLUDED)
8. SHIPPING WEIGHTS ARE BASED ON UNITS WITHOUT BURNER OR BURNER MOUNT.

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.